

# The Sentinel "Mini Key Safe" holds Credit Cards and up to 10 Keys and Automotive Key Fobs


Access for: Children, Vacation Property, Employees, Elderly Care & lots more...

## SENTINEL

Your sentry for safe entry



Storage Compartment



Setting Key

Yellow Dials



Yellow dial unset (Arrow towards you)

Yellow dial set (Arrow pointing away)



Using the pencil mark the position of the screw holes to be drilled

### NOTES:

1. You can change the combination for the Sentinel at any time.
2. We suggest that you mount your Sentinel in a discrete location away from direct view, such as porches, garage, out of direct eye line.
3. Keep shutter hatch closed to increase weather resistance and to conceal the dials from view.



### INSTRUCTIONS

#### Opening your Sentinel

1. Open the front cover from the top to reveal the push buttons and the opening lever.
2. When purchased, no combination is set, push down the opening lever to open.

#### Setting new combination for your Sentinel

1. Open the Sentinel door to reveal the setting mechanism.
2. Remove the setting key.
3. Choose a combination and write it down prior to setting the Sentinel. (A normal pin number is four digits, however we recommend using more numbers or choosing a name e.g DAVIS which would be 32847)
4. Using the setting key, turn the yellow dial of the chosen digit, e.g. 3, 180 degrees, so that the arrow is pointing away from you.
5. Repeat this for each chosen number/letter.
6. Test combination prior to closing the lid (see note 1)
  1. After setting if you push the opening lever, it will appear to be locked.
  2. Enter your combination to test the function.
  3. Re-enter combination and push lever to close.
7. Return setting key to original position for future use.

#### Wall Mounting your Sentinel

NOTE: you will require a X-head/Pozi screwdriver, pencil, a spirit level, drill bit, a drill and a hammer.

1. Open the Sentinel door, as above.
2. Position the Sentinel on the desired mounting surface (see note 2)
3. Use a spirit level to check that the Sentinel is vertical.
4. Mark the position of the screw holes on the desired surface.
5. Remove Sentinel.
6. Drill holes.
7. Use hammer to fit wall plug. (if necessary).
8. Position Sentinel.
9. Insert and tighten screws.
10. Close the storage compartment.



Insight Security, Unit 2, Cliffe Industrial Estate, Lewes, East Sussex, BN8 6JL

tel: 01273 475500 fax: 01273 478800, www.insight-security.com

