

When you're looking for quality performance from your DVR, but you're on a tight budget, this amazing unit fits the bill perfectly



DVR400

Easy to install and use, this low cost, 4 Channel DVR (Digital Video Recorder) is ideal for professional and domestic use. Featuring proven MJPEG compression it produces great picture quality and reliable performance.

Designed as a straight replacement for older style tape based CCTV recording systems, this DVR is ideal for a wide range of surveillance and security applications, and features 4 camera inputs and 2 composite video outputs.

Images are recorded onto the internal PC type Hard Drive and you choose whether to record in quad mode or record each camera individually and simultaneously (full duplex mux mode). You can search through recorded video footage easily and conveniently by "time and date", by "event", or using fast forward search.

KEY FEATURES

- MJPEG Algorithm compression
- Built-in Hard Drive (120GB or 250GB option)
- 4 channel video 25 fps recording capability
- 3 Recording quality settings and 4 frame rate options
- Simple on-screen menu setup
- Motion detection

Approx recording days (full duplex mux mode)

Recording quality	25fps	12fps	6fps	1fps
- with 120GB HDD				
High quality	3.9	7.8	15.6	97.0
Normal quality	5.6	11.2	22.5	140.0
Basic quality	7.4	14.8	29.6	184.0
- with 250GB HDD				
High quality	8.1	16.2	32.5	201.7
Normal quality	11.6	23.4	46.8	291.2
Basic quality	15.3	30.7	61.5	382.7

<u>Item</u>	<u>Specification</u>
Compression Method	MJPEG
On-board HDD capacity	120GB or 250GB
Video Input	4 channel (PAL / NTSC)
Video Out	2 x composite
Screen Modes	Full Screen or Quad display
Resolution - live video	720 x 576 pixels, real time Full Screen or Quad
Resolution - recording	640 x 272 pixels, Quad or Duplex MUX
Recording modes	Time, Motion, Schedule, Alarm
Motion Detection	yes
Recording Rate	up to 25fps (Quad) or 6.25fps MUX per camera
Recording Device	1 x 3.5" Internal HDD
Recording Quality	3 x selectable levels High, Normal, Basic
Video Input	BNC x 4, 1.0V p-p, 75 ohm
Main Monitor output	BNC x 2, 1.0V p-p, 75 ohm
Alarm input	4 x inputs, quick release terminals
Relay Output	1 (NO/NC)
Operation	Simplex
Password Protection	yes
Operating Temperature	0-40 C
Power / Consumption	12V / 5A (included)
Dimensions	300(W) x 65(H) x 200(D) mm
Weight	approx 3.5 Kg

